ENVIRONMENTAL AND LAND USE CRITERIA FOR TRANSMISSION LINE EVALUATION

Land Use

Length of alternative route

Number of habstable structures! within 300 feet of the right-of-way (ROW) centerline

Number of newly affected habitable structures' within 300 feet of ROW centerline

Length of ROW using existing transmission line ROW

Length of ROW parallel to existing transmission line ROW

Length of ROW parallel to other existing ROW (roadways, pipelines, railway, etc.)

Length of ROW parallel to apparent property lines2

Length of ROW through parks/recreational areas

Number of additional parks/recreational areas' within 1,000 feet of the ROW centerline

Length of ROW through cropland

Length of ROW through pasture/rangeland

Length of ROW through land irrigated by traveling systems (rolling or pivot type)

Number of pipeline crossings

Number of transmission line crossings

Number of U S and state highway crossings

Number of farm-to-market road (FM) crossings

Number of cemeteries within 1,000 feet of the ROW centerline

Number of FAA registered airports with at least one runway more than 3,200 feet in length located within 20,000 feet of the ROW centerline Number of FAA registered amports having no runway more than 3,200 feet in length located within 10,000 feet of the ROW centerline

Number of private airstrips within 10,000 feet of the ROW centerline

Number of heliports within 5,000 feet of the ROW centerline

Number of commercial AM radio transmitters within 10,000 feet of the ROW centerline

Number of FM radio transmitters, microwave towers, and other electronic installations within 2,000 feet of the ROW centerline

Estunated length of ROW within foreground visual zone* of US and state highways

Estimated length of ROW within foreground visual zone4 of FM roads

Estimated length of ROW within foreground visual zone⁵ of park/recreational areas³

Length of ROW through upland woodlands/brushland

Length of ROW through bottomland/riparian woodlands

Length of ROW across National Wetlands Inventory mapped wetlands

Length of ROW across known habitat of federally listed endangered or threatened species

Length of ROW through modeled potentially suitable habitat for Golden-cheeked Warbler Length of ROW across open water (lakes, ponds)

Number of stream crossings

Number of river crossings

Length of ROW parallel (within 100 feet) to streams or rivers

Length of ROW across 100-year floodplains

Area of ROW across Edwards Aquifer drainage zone (acres)

Cultural Resources

Number of recorded historic or prehistoric sites crossed by ROW

Number of additional recorded historic or prehistoric sites within 1,000 feet of ROW centerline

Number of National Register listed or determined eligible sites crossed by ROW

Number of additional National Register listed or determined eligible sites within 1,000 feet of ROW centerline

Length of ROW through areas of high archaeological/historic site potential

Single-family and multi-family dwellings, mobile houres, spartment buildings, commercial structures, midutinal structures, churches, hospitals, autsing homes, and schools or other structures normally inhabited by immans or infunded to be machine the same of a different pass within 300 feet of the centerline of a transmission project of 230-by or less.

Property innes created by exting reads, highway, or anional Stoyle are not without a collect observation and a servation an





AGENCIES and OFFICIALS CONTACTED

FEDERAL

- Federal Aviation Administration
- Federal Emergency Management Agency
 - Natural Resources Conservation Service
 - U.S. Army Corps of Engineers
- U.S. Environmental Protection Agency
 - U.S. Fish & Wildlife Service
- U.S. Senators and Congressional Representatives U.S. National Parks Service

- Railroad Commission of Texas
- Texas Commission on Environmental Quality
 - Texas Department of Transportation
 - >Aviation Division
- ≻Environmental Affairs Division
 - > Planning and Programming
 - - Texas General Land Office
- Texas Historical Commission
- Texas Parks & Wildlife Department Texas Water Development Board
 - State Senators and Representatives

- County Officials (Blanco, Gillespie, and Kendall)
 - City Officials (Fredericksburg)
- School ISDs (Blanco, Comfort, Fredericksburg, and Johnson City)
- Blanco, Gillespie, and Kendall Counties Economic Development Corporation
 - Blanco, Gillespie, and Kendall Counties Historical Commission
 - Alamo Area Council of Governments
- Capitol Area Council of Governments
- Fredericksburg Chamber of Commerce
 - Stonewall Chamber of Commerce



(This page left blank intentionally.)

Appendix C

(This page left blank intentionally.)

		Alternative Route 1	
	Segment Combination: A-B-	D-E-F-G-G3-H-L2-I2-I3-J-J2-L-E	32
	Substation Alternative: 1	and Tap Point Alternative: 4b	
Map Number	Approximate Distance from Route Centerline (feet)	Structure or Feature	Nearest Alternative Route Segment
1	159	Commercial	A
2	166	Commercial	Α
3	242	Single-family residence	A
7	161	Single-family residence	G3
8	187	Single-family residence	L2
11	222	Single-family residence	L2
12	242	Single-family residence	12
13	175	Single-family residence	13
15	264	Single-family residence	J2
17	158	Playhouse	L
18	136	Office	L
19	207	Single-family residence	L
	426	41KE18	13
	495	41KE19	J
	945	41KE20	J

^{*}Due to the potential horizontal inaccuracies of the aerial photography and data utilized, all habitable structures within 310' have been identified.

-D-R-R2-S-Q1-Z-Z1-Z3-C1-C2-E2 1 and Tap Point Alternative: 1 Structure or Feature	-G2
	Nearest Alternative Route Segment
Commercial	A
Commercial	A
	A
Single-family residence	R
Single-family residence	R
	R
	R2
	R2
	Z
	Z1
	Z1
	C2
	C2
Commercial	C2
School	C2
Single-family residence	E2
Single-family residence	E2
	E2
Single-family residence	E2
Williams Creek School	C2
	Z1
Otte	Z1
Kennedy Ranch	G2
41GL143	C1
	Commercial Commercial Single-family residence

^{*}Due to the potential horizontal inaccuracies of the aerial photography and data utilized, all habitable structures within 310' have been identified.

		y Alternative Route 3		
	Segment Combination: B-D-E-F-G-G3-H-L1-I-I3-K-K1-K2-L			
	Substation Alternative: 2	and Tap Point Alternative: 4a		
Map Number	Approximate Distance from Route Centerline (feet)	Structure or Feature	Nearest Alternative Route Segment	
7	161	Single-family residence	G3	
9	132	Single-family residence	L1	
10	274	Single-family residence	L1	
13	175	Single-family residence	13	
14	110	Single-family residence	K1	
15	221	Single-family residence	K1	
17	158	Playhouse		
18	136	Office		
19	207	Single-family residence		
No. See	426	41KE18	13	

^{*}Due to the potential horizontal inaccuracies of the aerial photography and data utilized, all habitable structures within 310' have been identified.

	Table 5-6 Prima	ry Alternative Route 4	
Segme		-R1-R2-S-Q1-Z-Z2-Z3-B1-F2-E	1-V1-S1-P1
		2 and Tap Point Alternative: 3	
Map Number	Approximate Distance from Route Centerline (feet)	Structure or Feature	Nearest Alternative Route Segment
37	188	Single-family residence	P1
38	285	Single-family residence	P1
40	132	Single-family residence	R2
41	254	Single-family residence	R2
44	224	Single-family residence	Z
47	215	Single-family residence	E1
303	472	FM radio transmitter and ASR Tower	B1
401	9,599	BurgAERO	Z2
402	1,001	Otte	Z2

^{*}Due to the potential horizontal inaccuracies of the aerial photography and data utilized, all habitable structures within 310' have been identified.

	Table 5-7 Prima	ry Alternative Route 5	***************************************
S	egment Combination: C-D-E	E-F-G-G3-H-L1-M1-I2-I3-K-H2-J	2-L-B2
	Substation Alternative:	3 and Tap Point Alternative: 4	b
Map Number	Approximate Distance from Route Centerline (feet)	Structure or Feature	Nearest Alternative Route Segment
7	161	Single-family residence	G3
9	132	Single-family residence	L1
10	274	Single-family residence	L1
11	296	Single-family residence	M1
12	242	Single-family residence	12
13	175	Single-family residence	
15	264	Single-family residence	J2
17	158	Playhouse	1
18	136	Office	
19	207	Single-family residence	
	426	41KE18	13

^{*}Due to the potential horizontal inaccuracies of the aerial photography and data utilized, all habitable structures within 310' have been identified.

	Table 5-8 Prima	ry Alternative Route 6	
	Segment Combination: C-D	-E-F-G-G3-U-Y2-N-G1-V1-H1-I1	I-G2-
	Substation Alternative:	3 and Tap Point Alternative: 1	
Map Number	Approximate Distance from Route Centerline (feet)	Structure or Feature	Nearest Alternative Route Segment
7	161	Single-family residence	G3
26	76	Single-family residence	Y2
27	155	Single-family residence	N
28	56	Single-family residence	N
48	139	Single-family residence	H1
57	68	Single-family residence	11
403	4,985	Kennedy Ranch	G2

^{*}Due to the potential horizontal inaccuracies of the aerial photography and data utilized, all habitable structures within 310' have been identified.

		ry Alternative Route 7	
	Segment Combination: F	-G-G3-H-L1-I-I3-K-K1-U1-N1-B	2
	Substation Alternative: 4	and Tap Point Alternative: 4b)
Map Number	Approximate Distance from Route Centerline (feet)	Structure or Feature	Nearest Alternative Route Segment
7	161	Single-family residence	G3
9	132	Single-family residence	L1
10	274	Single-family residence	L1
13	175	Single-family residence	13
14	110	Single-family residence	K1
15_	221	Single-family residence	K1
16	239	Guest house	N1
	426	41KE18	13

^{*}Due to the potential horizontal inaccuracies of the aerial photography and data utilized, all habitable structures within 310' have been identified.

	Table 5-10 Prima	ary Alternative Route 8	
	Segment Combination: F-	G-R1-R2-S-T-A1-F2-D1-F1-E2-	G2
	Substation Alternative:	4 and Tap Point Alternative: 1	
Map Number	Approximate Distance from Route Centerline (feet)	Structure or Feature	Nearest Alternative Route Segment
40	132	Single-family residence	R2
41	254	Single-family residence	R2
53	195	Single-family residence	E2
54	276	Single-family residence	E2
55	220	Single-family residence	E2
56	276	Single-family residence	E2
402	3,738	Otte	A1
403	4,985	Kennedy Ranch	G2
	124	41GL140	A1
	105	41GL397	D1
	470	41GL396	D1

^{*}Due to the potential horizontal inaccuracies of the aerial photography and data utilized, all habitable structures within 310' have been identified.

		ary Alternative Route 9	
Se		-C-M-N-P-B2-F2-B1-F1-J1-O1-I	
	Substation Alternative:	5 and Tap Point Alternative: 3	
Map Number	Approximate Distance from Route Centerline (feet)	Structure or Feature	Nearest Alternative Route Segment
7	161	Single-family residence	G3
9	132	Single-family residence	L1
10	274	Single-family residence	L1
20	56	Single-family residence	W1
21	151	Single-family residence	W1
22	222	Commercial	W1
23	226	Single-family residence	Y1
24	309	Single-family residence	Y1
25	273	Single-family residence	Y1
26	76	Single-family residence	Y2
27	155	Single-family residence	N
28	56	Single-family residence	N
29	145	Hunting Cabin	W
30	74	Single-family residence	W
31	186	Single-family residence	W
32	147	Single-family residence	X
33	115	Single-family residence	X
36	194	Single-family residence	X
304	1,399	Microwave and ASR Tower	W
305	446	ASR Tower	W

^{*}Due to the potential horizontal inaccuracies of the aerial photography and data utilized, all habitable structures within 310' have been identified.

	Table 5-12 Prima	ary Alternative Route 10	
		1-R2-S-Q1-Z-Z2-Z3-C1-D2-F1-	E2-G2
		5 and Tap Point Alternative:	
Map Number	Approximate Distance from Route Centerline (feet)	Structure or Feature	Nearest Alternative Route Segment
40	132	Single-family residence	R2
41	254	Single-family residence	R2
44	224	Single-family residence	Z
53	195	Single-family residence	E2
54	276	Single-family residence	E2
55	220	Single-family residence	E2
56	276	Single-family residence	E2
401	9,599	BurgAERO	Z2
402	1,001	Otte	Z2
403	4,985	Kennedy Ranch	G2
	252	41GL56	D2
	366	41GL142	D2
	269	41GL143	D2

^{*}Due to the potential horizontal inaccuracies of the aerial photography and data utilized, all habitable structures within 310' have been identified.

	Table 5-13 Prin	nary Alternative Route 11	
	Substation Alternative	tion: G3-H-L1-I-I3-K-K1-K2-L : 8 and Tap Point Alternative: 4	la .
Map Number	Approximate Distance from Route Centerline (feet)	Structure or Feature	Nearest Alternative Route Segment
7	161	Single-family residence	G3
9	132	Single-family residence	L1
10	274	Single-family residence	L1
13	175	Single-family residence	13
14	110	Single-family residence	K1
15	221	Single-family residence	K1
17	158	Playhouse	
18	136	Office	
19	207	Single-family residence	<u> </u>
	426	41KE18	13

^{*}Due to the potential horizontal inaccuracies of the aerial photography and data utilized, all habitable structures within 310' have been identified.

·	Table 5-14 Prin	nary Alternative Route 12	
	Segment Combination	: R1-R2-S-T-A1-F2-E1-V1-H1-	11
	Substation Alternative	e: 8 and Tap Point Alternative:	2
Map Number	Approximate Distance from Route Centerline (feet)	Structure or Feature	Nearest Alternative Route Segment
40	132	Single-family residence	R2
41	254	Single-family residence	R2
47	215	Single-family residence	E1
48	139	Single-family residence	H1
402	3,738	Otte	A1
Tue to the water tist	124	41GL140	A1

^{*}Due to the potential horizontal inaccuracies of the aerial photography and data utilized, all habitable structures within 310' have been identified.

		nary Alternative Route 13	
	Segment Combinat	tion: P-O1-Q-S-T-V-N-W-Y-X2	
	Substation Alternative	e: 6 and Tap Point Alternative:	3
Map Number	Approximate Distance from Route Centerline (feet)	Structure or Feature	Nearest Alternative Route Segment
27	155	Single-family residence	N
28	56	Single-family residence	N
29	145	Single-family residence	W
30	74	Hunting Cabin	W
31	186	Single-family residence	W
32	217	Single-family residence	Y
33	266	Single-family residence	Y
34	306	Single-family residence	Y
35	283	Single-family residence	Y
39	250	Commercial	P
304	1,399	Microwave and ASR Tower	W
305	446	ASR Tower	W
402	6,310	Otte	T

^{*}Due to the potential horizontal inaccuracies of the aerial photography and data utilized, all habitable structures within 310' have been identified.

Table 5-16 Primary Alternative Route 14 Segment Combination: P-O1-T1-Z-Z1-Z3-C1-C2-E2-G2				
Map Number	Approximate Distance from Route Centerline (feet)	Structure or Feature	Nearest Alternative Route Segment	
39	250	Commercial	Р	
42	199	Single-family residence		
43	151	Commercial	T1	
44	224	Single-family residence	Z	
45	205	Single-family residence	Z1	
46	94	Single-family residence	Z1	
49	87	Single-family residence	C2	
50	197	Commercial	C2	
51	162	Commercial	C2	
52	286	School C2		
53	195	Single-family residence E2		
54	276	Single-family residence E2		
55	220	Single-family residence E2		
56	276	Single-family residence E2		
301	1,666	ASR Tower	T1	
302	1,868	ASR Tower	T1	
401	8,468	BurgAERO	Z1	
402	0	Otte	Z1	
403	4,985	Kennedy Ranch	G2	
Oue to the petantial	535	41GL143	C1	

^{*}Due to the potential horizontal inaccuracies of the aerial photography and data utilized, all habitable structures within 310' have been identified.

	Table 5-17 Prin	nary Alternative Route 15	
		nation: O1-Q-S-T-V-N-O-N1	
	Substation Alternative	: 7 and Tap Point Alternative:	4a
Approximate Distance Map Number from Route Centerline Structure or Feature Nearest Alterna			Nearest Alternative Route Segment
16	239	Guest house	N1
27	155	Single-family residence	N
28	56	Single-family residence	N
402	6,310	Otte	T
404	1,952	Headwaters	0

^{*}Due to the potential horizontal inaccuracies of the aerial photography and data utilized, all habitable structures within 310' have been identified.

	Table 5-18 Prin	nary Alternative Route 16	
	Segment Combination	n: O1-Q-S-T-A1-F2-E1-V1-H1-J	1
		e: 7 and Tap Point Alternative:	
Map Number	Approximate Distance from Route Centerline (feet)	Structure or Feature	Nearest Alternative Route Segment
47	215	Single-family residence	E1
48	139	Single-family residence	H1
402	3,738	Otte	A1
	124	41GL140	A1

^{*}Due to the potential horizontal inaccuracies of the aerial photography and data utilized, all habitable structures within 310' have been identified.

	Table 5-19 Prin	nary Alternative Route 17	
	Segment Comb	oination: S-T-V-N-W-X-X2	
· · · · · · · · · · · · · · · · · · ·	Substation Alternative	e: 9 and Tap Point Alternative:	3
Map Number	Approximate Distance from Route Centerline (feet)	Structure or Feature	Nearest Alternative Route Segment
27	155	Single-family residence	N
28	56	Single-family residence	N
29	145	Single-family residence	W
30	74	Hunting Cabin	W
31	186	Single-family residence	W
32	147	Single-family residence	X
33	115	Single-family residence	X
36	194	Single-family residence	X
304	1,399	Microwave and ASR Tower	
305	446	ASR Tower	W
402	6,310	Otte	W T

^{*}Due to the potential horizontal inaccuracies of the aerial photography and data utilized, all habitable structures within 310' have been identified.

	Table 5-20 Prin	nary Alternative Route 18	
		S-Q1-Z-Z2-Z3-B1-F2-D1-F1-E2	-G2
	Substation Alternative	e: 9 and Tap Point Alternative:	1
Map Number	Approximate Distance from Route Centerline (feet)	Structure or Feature	Nearest Alternative Route Segment
44	224	Single-family residence	Z
53	195	Single-family residence	E2
54	276	Single-family residence	E2
55	220	Single-family residence	E2
56	276	Single-family residence	E2
303	FM madia to a second title		B1
401	9,599	BurgAERO	Z2
402	1,001	Otte	Z2 Z2
403	4,985	Kennedy Ranch	G2
	470	41GL396	D1
	105	41GL397	D1

^{*}Due to the potential horizontal inaccuracies of the aerial photography and data utilized, all habitable structures within 310' have been identified.

	Table 5-21 Prin	nary Alternative Route 19	
	Segment Combi	nation: G3-U-Y2-N-W-Y-X2	
	Substation Alternative	e: 8 and Tap Point Alternative:	3
Map Number	Approximate Distance from Route Centerline (feet)	Structure or Feature	Nearest Alternative Route Segment
7	161	Single-family residence	G3
26	76	Single-family residence	Y2
27	155	Single-family residence	N
28	56	Single-family residence	N
29	145	Single-family residence	W
30	74	Hunting Cabin	W
31	186	Single-family residence	W
32	217	Single-family residence	Y
33	266	Single-family residence	Y
34	306	Single-family residence	Ÿ
35	283	Single-family residence	Y
304	1,399	Microwave and ASR Tower	w
305	446	ASR Tower	W

^{*}Due to the potential horizontal inaccuracies of the aerial photography and data utilized, all habitable structures within 310' have been identified.

	Table 5-22 Prin	nary Alternative Route 20	
	Segment Combination	n: R2-R1-G3-H-L1-I-I3-K-K2-L-E	32
	Substation Alternative	: 9 and Tap Point Alternative:	4b
Map Number	Approximate Distance from Route Centerline (feet)	Structure or Feature	Nearest Alternative Route Segment
7	161	Single-family residence	G3
99	132	Single-family residence	L1
10	274	Single-family residence	L1
13	175	Single-family residence	13
14	110	Single-family residence K1	
15	221	Single-family residence K1	
17	158	Playhouse L	
18	136	Office	i
19	207	Single-family residence L	
40	132	Single-family residence	R2
41	254	Single-family residence R2	
402	9,761	Otte R2	
	426	41KE18	13

^{*}Due to the potential horizontal inaccuracies of the aerial photography and data utilized, all habitable structures within 310' have been identified.

Appendix D

Figure 4-8

(This page left blank intentionally.)

THIS PAGE CONTAINS
COLOR MAPS OR
DRAWINGS
AND
CAN BE VIEWED
IN

(PUBLIC UTILITY COMMISSION OF TEXAS 1701 N. CONGRESS AVENUE AUSTIN, TX 78701)

CENTRAL RECORDS

THIS PAGE CONTAINS
COLOR MAPS OR
DRAWINGS
AND
CAN BE VIEWED
IN

CENTRAL RECORDS

(PUBLIC UTILITY COMMISSION OF TEXAS 1701 N. CONGRESS AVENUE AUSTIN, TX 78701)

Appendix E

Figure 5-1

(This page left blank intentionally.)

THIS PAGE CONTAINS
COLOR MAPS OR
DRAWINGS
AND
CAN BE VIEWED
IN

(PUBLIC UTILITY COMMISSION OF TEXAS 1701 N. CONGRESS AVENUE AUSTIN, TX 78701)

CENTRAL RECORDS

THIS PAGE CONTAINS
COLOR MAPS OR
DRAWINGS
AND
CAN BE VIEWED
IN

CENTRAL RECORDS

(PUBLIC UTILITY COMMISSION OF TEXAS 1701 N. CONGRESS AVENUE AUSTIN, TX 78701) Appendix F
LCRA TSC's Oak Wilt Policy

(This page left blank intentionally.)

LCRA EMPLOYEE POLICY MANUAL: 400 SAFETY AND ENVIRONMENTAL Requirement 402R2: Oak Wilt Prevention				
Approval Date October 2014 Owner Manager, Environmental Affairs				
Effective Date	October 2014	Policy Owner Review	Every Three Years	
Review Date	October 2014	Next Executive Team or Designee Review	2016	

402R2.1 Oak Wilt Defined

Oak wilt is a tree disease caused by the fungus *Ceratocystis fagacearum*. The fungus infects the conductive tissue (xylem) that contains vessels to transport moisture throughout the tree. The oak wilt fungus causes the infected tree to produce tylosis, which becomes so significant the tree can no longer transport water through its vascular system. The end result, in most cases, is a dead tree.

402R2.2 Prevention of Oak Wilt

- Any person representing LCRA involved in field work where oak trees are trimmed, removed, or could be potentially wounded shall receive oak wilt training. LCRA representatives required to have training include, but are not limited to, project managers, construction managers, environmental staff, equipment operators, contractors, subcontractors, and volunteers. Training must occur before field work may begin in areas with oak trees. Those working with oak trees shall complete the LCRA Oak Wilt Prevention Report as well. When possible, oak trees should not be trimmed or pruned between February and June.
- At all times, sterilizing equipment and dressing wounds are mandatory when trimming or pruning susceptible species.
- Sterilizing tree removal and trimming equipment will occur before leaving the project area or between property boundaries, and will involve using either 1) aerosol disinfectant; 2) 10 percent bleach-water solution; or 3) isopropyl alcohol (minimum 70 percent). In addition, tree-trimming equipment must be sterilized thoroughly before it is used again.
- Irrespective of limb size, all cuts and wounds must be painted with a wound or latex-based paint, a product approved by a certified arborist who has obtained an Oak Wilt Specialist Certification, or one recommended by the Texas Forest Service. Such painting will include stump cuts and damaged roots (regardless if the stumps are to remain in place or are to be grubbed), both above and below ground. Damaged roots located in a trench or excavations that a safety supervisor says cannot be accessed safely do not have to be painted. It takes only a few minutes for an open tree wound to attract insects, so painting cannot wait until all pruning is accomplished. Wound protection must be applied immediately. At a minimum, LCRA representatives will seal all wounds of any size on all oak trees. However, LCRA representatives may elect to seal cuts of other hardwood trees on a case-by-case basis.

402R2.3 Disposal

- Chipping or shredding the wood from infected trees to use as mulch is an acceptable means of recycling it.
 Chipping or shredding dries the wood quickly and kills the fungus.
- Burning diseased wood is an acceptable means of disposal. Burning diseased logs kills the oak wilt fungus, and it cannot be spread by smoke.
- Firewood from diseased trees should not be stored near healthy trees because fungal spores or insects that carry
 the spores can spread the fungus. If the brush or logs are to be left for firewood, the LCRA representative must
 explain to the landowner or landowner's representative that the brush or logs may be infected and warn them of
 storage hazards.
- LCRA representatives may fulfill this landowner notification obligation by providing pertinent information regarding burning and firewood to the landowner or landowner's representative. Logs over 4 inches, or 10

- centimeters, in diameter at breast height must be girdled (have the bark removed), as fungal mats have been found on logs this size and larger after the tree was felled.
- It is recommended that oak firewood be stored under a sheet of clear plastic, and edges tightly sealed with soil or bricks. That should prevent any spore-carrying beetles from escaping. Use clear plastic because black plastic will reveal any escape holes to the beetles.
- Unused disinfectants and paints must be recycled or disposed of properly.
- Material Safety Data Sheets (MSDS) are required for each paint and disinfectant used.

See Also:

LCRA Oak Wilt Prevention Report

LCRA Oak Wilt Prevention Report

Oak wilt is a tree disease caused by a fungus which in most cases kills the tree. To help prevent the spread of oak wilt LCRA's Oak Wilt Policy states that all wounds made to oak trees must be painted as soon as the wound is created with a wound or latex-based paint or a Sterilization of tree removal and trimming equipment must occur before leaving the project area or between property boundaries and must involve using an aerosol disinfectant, ten (10) percent bleach-water solution, or isopropyl alcohol (minimum 70%). Tools must be product approved by a Certified Arborist who has obtained an Oak Wilt Specialist Certification or as directed by the Texas Forest Service. disinfected between trees if pruning adjacent to oak wilt infested areas. In addition, trimming equipment must be sterilized thoroughly before it is used again. If mechanical clearing occurs using a device such as a flail mower, one must ensure that stumps are painted.

Aerosol / Bleach / Alcohol Aerosol / Bleach / Alcohol Aerosol / Bleach / Alcohol Bleach / Alcohol Aerosol / Bleach / Alcohol Bleach / Alcohol Bleach / Alcohol Aerosol / Bleach / Alcohol Type of Disinfectant Used (circle one) *It is highly recommended that a dark-colored paint (black or brown) be used. Marking and other types of paints that fade easily are not recommended. Aerosol / Aerosol / Aerosol / # of Oak Trees **Painted** Color of Paint* Please fill out the following report to ensure compliance with LCRA's Oak Wilt policy. Paint used (attach MSDS) Type of Structures (if applicable) Parcel# (if known) Land County (e.g. TL #, Substation, Location Project Park, etc.) Workers Name (printed); Date

Please return to your LCRA Environmental Representative


Revision Date: October 15, 2014

Company:

Date:

Workers Signature:

(This page left blank intentionally.)



February 13, 2013

Mr. Ross Phillips Vice-President and Chief Operating Officer LCRA Transmission Services Corporation PO Box 220 Austin, Texas 78767

Dear Mr. Phillips:

For several years now, CTEC staff has been working with LCRA TSC staff on projects that improve service for its members in the CTEC service area around Fredericksburg and provides a solution to a violation of planning criteria at CTEC's Goehmann Lane substation. These projects include:

- 1) The construction of a new distribution substation at the LCRA TSC Gillespie Substation.
- 2) The construction of a new Hollmig 138 kV/24.9 kV transmission and distribution substation.
- 3) The refurbishing and construction of a distribution substation at the existing LCRA Nebo substation.
- 4) The construction of a new 138 kV/24.9 kV substation in or near Blumenthal, located between Fredericksburg and Stonewall.

The first two projects are complete and the Nebo project is scheduled to be completed by late May of this year. The Blumenthal project remains to be completed and is the primary focus of this letter.

CTEC staff has worked with LCRA TSC staff to investigate distribution alternatives and CTEC has delivered its findings to LCRA TSC staff for review and comment. CTEC is of the opinion that, based on its findings for distribution alternatives, the Blumenthal project should be pursued and constructed. This project would involve a new radial 138 kV transmission line to serve a new 138 kV/24.9 kV distribution substation in the vicinity of Blumenthal. In support of CTEC's planning efforts, CTEC has previously included a new substation in the Blumenthal area in its Board approved 2008-2027 Twenty Year Long Range Study and has included this project in its current Board approved 2013-2016 System Improvements Work Plan.

CTEC recognizes that the construction of a new 138 kV transmission line by LCRA TSC will require a filing with the Public Utility Commission of Texas for an amendment to its Certificate of Convenience and Necessity and is prepared to assist LCRA TSC in this effort with whatever resources are necessary to accomplish the filing.

386 Friendship Lane • Fredericksburg, Texas • Telephone 830-997-2126 • Toll Free 800-900-CTEC (2832) • www.ctec.coop

Based on existing reliability concerns and anticipated continued electric load growth for the CTEC service area east of Fredericksburg, CTEC needs the Blumenthal substation project with its related LCRA TSC 138 kV transmission line and would like to ensure plans are timely completed by LCRA TSC to meet the continued need for reliable electric service to CTEC customers.

Sincerely,

Robert Loth III

Chief Executive Officer

Cc: CTEC Board of Directors



LCRA TRANSMISSION SERVICES CORPORATION

February 28, 2013

Mr. Robert A. Loth III Chief Executive Officer Central Texas Electric Cooperative, Inc. P.O. Box 553 Fredericksburg, Texas 78624-0553

Dear Bob:

Thank you for your letter of February 13 outlining the collaborative efforts of Central Texas Electric Cooperative, Inc. (CTEC) and LCRA Transmission Services Corporation (LCRA TSC) to address electric service reliability in Central Texas. CTEC and LCRA TSC have worked well together through our joint planning and project execution processes, and we look forward to working with CTEC staff to continue with the project's post planning phase.

As the next major milestone associated with this project, LCRA TSC will request a review by the Electric Reliability Council of Texas (ERCOT) Regional Planning Group. We plan to submit this request to ERCOT in April. Typically it takes about four weeks for ERCOT to complete this type of project review. Sergio Garza, Manager of System Planning and Protection, will work with David Peterson of your staff to communicate specific post planning project related activities and related schedules.

Should you have questions, please feel free to contact me at 1-800-776-5272, ext. 3360, or Sergio Garza at ext. 4149.

Sincerely,

Ross Phillips

Executive Manager, Transmission Services

Estimated Costs for Transmission Line, Tap Point (Switching Substation) and Substation Facilities Blumenthal CCN Application, Attachment 3

	T DIGIT.	Talisifilission	Switchi (Switchi	vitching Substat	ion) and Subst	ing Substation) and Substation Facilities Total Estimated Costs- Poles (Recommanded Structure T.	otal Estimated (Costs- Poles (Rec	ommended C+	F C	
Route	gns	Тар	Length (miles)	Estimated Total Cost	Right-of-Way & Land Acquisition	Right-of-Way Engineering & & Land Design	Engineering & Design	Procurement of Material &	Construction of Facilities	Construction of Facilities	100
1-Pole	+	4h	10.44		Homehou	(Ountry)	(Contract)	Equipment	(Utility)	(Contract)	<u> </u>
2-Pole*	_	-	13.44	\$34,779,000	\$7,662,000	\$4,046,000	\$1.080.000	\$8 722 000	1700	(
3-Pole		- ,	15.17	\$37,509,000	\$8,490,000	\$4,382,000	\$1 128 000	90,722,000	\$817,000	\$10,819,000	\$3,633,000
*0007	10	48	11.21	\$28,661,000	\$5,416,000	\$3 828 000	64 040 000	90,013,000	\$1,050,000	\$12,275,000	\$2,173,000
DO L	7	က	16.19	\$35,474,000	\$7.857.000	\$4.022,000	000,810,14	\$5,602,000	\$955,000	\$8,363,000	\$3.478.000
3-role	က	4p	11.98	\$31,009,000	\$6 Dec 000	000,772,50	\$1,154,000	\$6,526,000	\$797,000	\$11,494,000	\$3.389.000
6-Pole*	က	1	16.97	\$37,132,000	\$7.583,000	95,091,000	\$1,041,000	\$6,088,000	\$817,000	\$9,253,000	\$3 850 000
-Pole	4	4p	11.56	\$29,695,000	\$5 562 000	94,563,000	\$1,174,000	\$7,802,000	\$1,050,000	\$10.968 000	\$3,000,000
8-Pole*	4	1	15.83	\$36,098,000	\$8 395,000	\$3,847,000	\$1,028,000	\$5,837,000	\$817,000	\$8.731.000	\$3 872 000
9-Pole	5	3	11.62	\$28,510,000	&F 963 000	94,449,000	\$1,142,000	\$7,661,000	\$1,050,000	\$11 172 000	43,575,000
10-Pole*	5	1	16.56	\$40,000,000	000,000,000	\$3,812,000	\$1,029,000	\$5,599,000	\$797,000	\$0 470 000	000,822,24
11-Pole	8	49	10.40	440,030,000	\$8,099,000	\$4,521,000	\$1,162,000	\$8,295,000	\$1 050 000	#8, 178,000 #49,000	\$2,231,000
12-Pole*	α		10.40		\$4,529,000	\$3,745,000	\$995,000	\$5 324 000	000,000,100	\$13,068,000	\$2,903,000
13-Pole*		7	14.96	\$31,174,000	\$6,760,000	\$4,164,000	\$1 118 000	000,420,000	000,008	\$7,575,000	\$4,044,000
14-Polo	٥	8	10.91	\$25,381,000	\$4,842,000	\$3 749 000	94, 13,000	\$5,874,000	\$833,000	\$9,568,000	\$2,757,000
47 Dolo.*	0 1	-	12.87	\$32,789,000	\$6,804,000	\$4 153 000	91,010,000	\$5,238,000	\$797,000	\$8,224,000	\$1,521,000
13-10E	1	4a	13.26	\$30,676,000	\$5,326,000	\$4 040 000	\$1,002,000	\$7,260,000	\$1,050,000	\$10,037,000	\$2,423,000
47 Oct 47 A		2	12.81	\$27,106,000	\$5.374,000	\$3.951.000	000,270,000	\$5,988,000	\$955,000	\$9,711,000	\$3,584,000
-Lone	ာ	3	10.36	\$24,458,000	\$4 427 000	90,001,000	000,000,14	\$5,452,000	\$833,000	\$8,155,000	\$2 281 000
18-Pole*	တ	_	14.65	\$35,176,000	\$7.780.000	93,084,000	\$993,000	\$5,096,000	\$797,000	\$7.916.000	\$4 F2F 000
19-Pole	8	3	11.23	\$27.051.000	44 999 999	\$4,332,000	\$1,109,000	\$7,603,000	\$1.050,000	\$10.950.000	000,000
20-Pole	0	46	13.27	422 400 000	\$4,620,000	\$3,780,000	\$1,016,000	\$5,459,000	\$797,000	000,000,000	\$4,003,000
*Segment Q1.S T Ll and V may require less.	S.T.U. and V.m.	ov rock line less	17.01		\$6,374,000	\$4,017,000	\$1,075,000	\$6 254 DOD	907,000	90,080,000	\$2,484,000
		ay require lov	/-profile structu		outes that utiliz	Ze Segment 0.1 o		000,503,000	\$617,000	\$9,588,000	\$4,065,000
						Simon & i.o. i.o and v are partially estimated with H-frames.	i, co and vare	oartially estimate	ed with H-frame		

	Other			\$1,535,000	\$1,521,000	\$2,484,000	\$2,281,000	\$4.044.000	\$2 234 000	42 479 000	\$3,470,000	\$3,873,000	\$3,584,000	\$3,850,000	\$2,757,000	\$4 085 000	\$2,423,000	\$3 633 000	\$2 863 000	\$3.369.000	900,000	\$2,223,000	43,334,000	\$2,173,000	\$2,903,000
	Construction of Facilities	(Contract)	\$7 040 000	000,018,74	\$8,224,000	\$8,695,000	\$8,155,000	\$7,575,000	\$9.179,000	\$8.363.000	40,724,000	000,137,04	\$9,711,000	\$9,253,000	\$9,568,000	\$9,588,000	\$10,037,000	\$10,819,000	\$10,950,000	\$11,494,000	\$11 172 000	\$10 968 000	642 275 000	912,273,000	\$13,008,000 S.
ted Least to Mo	Construction of Facilities	(Utility)	\$797 000	8707 000	4/8/,000	\$797,000	\$833,000	\$955,000	\$797,000	\$955,000	\$817 000	000, 1000	4833,000 4833,000	\$817,000	\$833,000	\$817,000	\$1,050,000	\$817,000	\$1,050,000	\$797,000	\$1,050,000	\$1,050,000	\$1.050.000	\$1,050,000	ed with H-frame
osts- Poles (Sor	Procurement of Material &	Equipment	\$5,096,000	\$5 238 000	\$5 450 000	400,400,000	\$5,45Z,000	\$5,324,000	\$5,599,000	\$5,602,000	\$5,837,000	\$5.988.000	\$6.088,000	40,000,000	\$5,874,000	\$6,254,000	\$7,260,000	\$6,722,000	\$7,603,000	\$6,526,000	\$7,661,000	\$7,802,000	\$8,013,000	\$8.295.000	partially estimate
ıtal Estimated C	Engineering & Design	(Contract)	\$993,000	\$1,010,000	\$1.016.000	\$4 080,000	\$00E,000	000,0884	\$1,029,000	\$1,019,000	\$1,028,000	\$1,072,000	\$1,041,000	\$4 448 000	000,010,000	\$1,075,000	\$1,062,000	\$1,080,000	\$1,109,000	\$1,154,000	\$1,142,000	\$1,174,000	\$1,126,000	\$1,162,000	,T,U and V are
Table 2: Transmission, Tap Point (Switching Substation) and Substation Facilities Total Estimated Costs- Poles (Sorted Least to Mact Evangement)	Right-of-Way Engineering & & Land Design	(Othlity)	\$3,694,000	\$3,749,000	\$3,780,000	\$3.951,000	\$3.745.000	\$3 842 000	40,012,000	\$3,828,000	\$3,847,000	\$4,040,000	\$3,891,000	\$4.164.000	64 047 000	000,710,4	94,153,000	\$4,046,000	94,552,000	94,277,000	\$4,449,000	\$4,563,000	\$4,382,000	\$4,521,000	Therefore, routes that utilize Segment Q1,S,T,U and V are partially estimated with H-frames.
ion) and Substa	Right-of-Way & Land Acquisition	ilounda de	\$4,427,000	\$4,842,000	\$4,820,000	\$5,374,000	\$4,529,000	\$5.863.000	\$5.418.000	40,000	000,200,00	\$5,326,000	\$6,069,000	\$6,760,000	\$6.374,000	\$6 804 000	\$7,667,000	\$7.269.000	\$7,857,000	\$8.305.000	#0,030,000 #7,500,000	\$7,383,000 \$8,488,889	90,480,000	\$9,099,000	routes that utiliz
itching Substati	Estimated Total Cost	424 450 000	\$24,430,000	925,381,000	\$27,051,000	\$27,106,000	\$27,167,000	\$28,510,000	\$28.661,000	\$29 695 000	420 670 000	930,076,000	\$31,009,000	\$31,174,000	\$32,190,000	\$32.789.000	\$34.779.000	\$35,176,000	\$35.474.000	\$36,098,000	\$37 132 000	\$37 500 000	640,000,000	940,098,000	ıres. I herefore,
, Tap Point (Sw	Length (miles)	10.36	1004	1,00	11.23	12.81	10.40	11.62	11.21	11.56	13.26	44.00	1.98	14.96	13.27	12.87	13.44	14.65	16.19	15.83	16.97	15.17	18 58	OC.O.	יי-טוטוופ אוועכור
Transmission	Тар	က	c	0 0	2	7	4a	3	4a	49	43	4	2 c	7 :	4 0	1	4b	-	3	_	1	1	-	nav require lo	(a) a a b c c c c c c c c c
Table 2:	Sub	თ	9	8	2		١	٥	2	4	7	6	α		6	9	7	O	2	4	3	1	5	S.T.U and V.	
	Route	17-Pole*	13-Pole*	19-Pole	16-Pole*	11-Polo		a-Loie	3-Pole	7-Pole	15-Pole*	5-Pole	12-Pole*	20.Pole	201 010	14-Pole	1-Pole	18-Pole*	4-Pole*	8-Pole*	6-Pole*	2-Pole*	10-Pole*	*Segment Q1,	

		Other.		\$3,409,000	\$1,949,000	\$2 985 000	\$2,876,000	\$3 220 000	42,320,000	93,470,000	\$3,190,000	\$1.546,000	\$1 525 000	407,020,000	#4, 197, UUU	\$2,985,000	\$1,698,000	\$703.000	\$1 805 000	\$2,000,000	44,011,000	\$1,508,000	\$651,000	\$1,979,000	\$1,425,000
•	Construction	(Contract)	(Solitiaci)	\$10,364,000	\$11,820,000	\$7,908,000	\$11,039,000	\$8.798.000	\$10 513 000	\$ 575,000	\$8,276,000	\$10,717,000	\$8.724.000	\$12 613 000	\$7 420 000	47,120,000	\$9,113,000	\$7,769,000	\$9.582,000	\$9 256 000	\$7 700,000	47,700,000	\$7,461,000	\$10,495,000	\$8,240,000
	Construction of Facilities	(Utility)		\$0	\$0	\$0	\$0	\$0	\$0	Ç	0	Q\$	\$0	\$0	O\$	6	Q.	\$0	\$0	\$0	O\$	S	9 6	000	O#
	ocurement Material &	Equipment	0.00	\$3,818,000	\$4,401,000	\$2,877,000	\$4,180,000	\$3,184,000	\$4,190,000	\$2.933.000	0000000	000,840,44	\$3,253,000	\$4,683,000	\$2,599,000	\$3 545 000	000,010,000	\$4,882,000	\$3,648,000	\$3,263,000	\$3,023,000	\$2.750.000	\$3 991 000	\$3 113 000	#3 2F0 000
Total Costs De	Engineering & Design	(Contract)	\$787 000	900,000	9613,000	\$/06,000	\$841,000	\$728,000	\$861,000	\$715,000	\$829,000	9740,000	000,0174	\$849,000	\$682,000	\$805.000	\$607,000	422,000	9/48,000	\$759,000	\$747,000	\$680,000	\$796,000	\$703,000	\$762,000
Table 3: Transmission Facilities Estimated Total Cont.	Right-of-Way Engineering & & Land Design	(Utility)	\$3.446,000	\$3.845.000	45,515,000	45,415,000	#3,720,000	93,291,000	\$3,796,000	\$3,247,000	\$3,682,000	\$3.255.000	92 171 000	93,754,000	\$3,130,000	\$3,594,000	\$3,192,000	\$3 386 000	000,000,00	43,425,000	\$3,381,000	\$3,137,000	\$3,565,000	\$3,223,000	\$3,417,000
ansmission Faci	Right-of-Way	Acquisition	\$7,465,000	\$8.240.000	\$5 219 000	\$7,668,000	\$5,872,000	47 333 000	000,000,000	000,000,00	\$8,145,000	\$5.674.000	\$8 849 000	900,049,000	94,332,000	\$6,563,000	\$4,653,000	\$6.554,000	\$5 129 000	\$5 477 000	000,77,000	\$4,238,000	\$7,019,000	\$4,631,000	\$6,177,000
Table 3: Tr	Estimated Total Cost		\$29,269,000	\$30,838,000	\$22,908,000	\$30,324,000	\$25,201,000	\$30,163,000	\$23,726,000	\$20,000 \$00,000	\$28,968,000	\$23,147,000	\$32,945,000	\$20 848 000	\$35 240 000	000,010,000	\$19,906,000	\$25,524,000	\$24,643,000	\$21,536,000	\$18 047 000	\$27,047,000	\$41,845,000	\$21,335,000	\$26,020,000
	Length (miles)	77 07	13.44	15.17	11.21	16.19	11.98	16.97	11.56	15.83	20.03	11.62	16.56	10.40	14 06	200		12.87	13.26	12.81	10.36	14.65	2 5	11.23	13.27
	. Tap	4	<u>-</u>		4a	3	49	-	4p	-	,	2	_	4a	2	6	5),		4a	2	8	-	6	2	2
	Sub	ļ.,	,	- -	2	2	3	က	4	4	ц		2	8	8	œ	0	اد		7	6	6	80	O	V Land II T O
	Route	1-Pole	2-Pole*	200	alor-o	4-Pole"	5-Pole	6-Pole*	7-Pole	8-Pole*	9-Pole	*0.00	alor-ole	11-Pole	12-Pole*	13-Pole*	14-Pole	45 0 21 *	in-Fole:	16-Pole*	17-Pole*	18-Pole*	19-Pole	20-Pole	*Segment O1 S T11

\$9,133,000 *Segment Q1,S,T,U and V may require low-profile structures. Therefore, routes that utilize Segment Q1,S,T,U and V are partially estimated with H-frames.

\$3,181,000

Table 4: Substation Facilities Estimated Total Costs*


Right-of-								
Engineering & I	Way & Land Acquisition	Engineering & En Design (Utility)	<u>ш</u> ~	Engineering & Design (Contract)	Procurement of Material & Equipment	Construction of Facilities	Construction of Facilities	Other ¹
	6400 000	†				(crinty)	(contract)	
- 1	000,001	#304,000		\$313.000	\$1.768.000	000 000		
\$3,656,000 \$100,000 \$304,000	\$100,000	\$304 000		4040	000,00	\$223,000	\$455,000	\$224,000
		000,		9513,000	\$1,768,000	\$223,000	\$455,000	4100 000
43,000,000 \$304,000 \$304,000	\$100,000 \$304,000		٠.	\$313 000	\$4 780 000		000,000	9483,000
+	\$100,000	+	1	200,0	000'00''	\$223,000	\$455,000	\$522,000
400,400	400,400	-	À	\$313,000 <u> </u>	\$1.768,000	\$223 000	000	
\$3,869,000 \$100.000 \$304 000	\$100.000 \$304 000	L	6	040 040		9220,000	\$455,000	\$683,000
000,1000	000,1000	+	9	9515,000	\$1,768,000	\$223.000	\$455,000	4700 000
\$3,301,000 \$100,000 \$304,000 \$3	\$100,000 \$304,000	_	83	\$313 000	\$1 7gp 000		000,000	000'00/¢
+	\$100,000	+	1	200,00	000,007,19	\$223,000	\$455,000	\$818,000
Opp'topp	Opp'topp	+	4	9313,000	\$1,768,000	\$223.000	\$455,000	4770 000
\$4,444,000 \$100,000 \$304,000 \$	\$100,000 \$304,000		Ù	\$313,000	\$4 700 000		000,000	9773,000
+	\$100 000 \$25.55	+	Ί	200,0	000,007,14	\$223,000	\$455.000	\$1 050 000
000,4004	200	9504,000		\$313,000	\$1.768 000	\$222 CCC	1	000,000
*Includes both OTFO					000,000	\$243,000 I.	2427 000	COC FOOD

*Includes both CTEC and LCRA Costs 1. CTEC's distribution circuit costs to build out the planned four circuits out of each sub site.

Each site has a mixture of re-building existing lines and new line.

5
1
T Pa
imat
S Est
Facilitie
station)
Subs
ching
Swit
oint (
Гар
able 5: I
ă
ŀ

				_		,		_	_	_			_
	Other			0) A		0) #		2	e G	9
•	Construction of Facilities	(יסטווומכו)		9	0	Ç	Ç.	O \$	O.	0	9	0\$	2
ביים ביים ביים ביים	Construction of Facilities (Ufility)	(fa)		\$827,000	2001	\$610,000	000,0104	\$574 000	2001	\$732,000	200120:1	\$594,000	
	Engineering & Engineering Procurement Construction Design & Design of Material & of Facilities of Facilities (Utility) (Contract) Equipment (Utility)		000,700,70	91,844,000		\$661,000		\$578,000	1000	000,7588		91,136,000	
	Engineering & Design (Contract)		C#	0	é	O A	é	چ	é	9	00	9	
	Engineering & Design (Utility)		\$463,000	20015	\$266,000	, CO, CO	\$253,000	\$20,000	\$311 000	0001	\$296,000	200,000	
	Kight-of- Way & Land Acquisition		\$150,000		\$97.000		\$89,000		\$97,000		\$97,000		
	Estimated Total Cost	200 100 04	33,284,000	400,000	91,534,000		\$1,484,000	1000	97,000,780,000	00 00 F 04	\$4,123,000		
	Tap Site	*	-	c	7	c	?	4	4	4	7	,	



Transmission lines and substations located in Gillespie County near the vicinity of the Proposed Project area.

BLUMENTHAL

Substation and Transmission Line Addition

RECOMMENDATION

This is a joint project plan developed by LCRA TSC and Central Texas Electric Cooperative (CTEC).

The project consists of constructing a new 138-kV transmission line from a new distribution substation (Blumenthal Substation) to a tap point on the existing Kendall – Mountain Top 138-kV transmission line.

The recommended project completion year is 2018. The total project cost is estimated at \$24,915,000.

This project will require certification by the Public Utility Commission (CCN).

PROJECT SCOPE

CTEC will construct the Blumenthal Substation consisting of a 12/16/20 MVA power transformer and associated low voltage delivery facilties. LCRA TSC will provide the 138-kV facilties.

LCRA TSC will construct a new 11.5-mile (approximate) 336 ACSR 138-kV transmission line (rated 129 MVA) from the new Blumenthal Substation to a switched tap point on the existing LCRA TSC's Kendall – Mountain Top 138-kV transmission line.

NEED FOR PROJECT

The need for this new load-serving substation and related new transmission line is driven by local load growth that is:

- located over a broad area that spans portions of three counties;
- located generally southeast of the City of Fredericksburg remote from the nearest available transmission source (Goehmann Lane Substation);
- served by a single 69-kV line;
- connected as part of a broader 69-kV system that has limited 138-kV support;
- anticipated to exceed the area's distribution capacity and reliability standards.

The area in southeastern Gillespie County, western Blanco County, and northern Kendall County is served by the Goehmann Lane Substation (see Figure 1). The load in this area has been growing at a high rate over the last few years and coupled with existing need for service in the area of southeastern Gillespie County and the remoteness to the Goehmann Lane Substation, the present delivery system's capability

Blumenthal 1 April 19, 2013

to reliably and adequately serve the load will be soon exceeded. The peak load in this winter peaking area grew approximately 11 percent between 2006 and 2011. The area consists of several small communities located generally south of State Highway 290 between Fredericksburg and Johnson City. Significant commercial development in the form of wineries is also located in this area. In terms of meter growth (new end-use customers), over the last 12 years this specific area has grown at a rate that is three times the overall CTEC system meter growth rate and projected to continue.

Commercial developments, many in the form of wineries, have been attracted to this area in part due to the area's climate and soil required for this industry as well as proximity to a major thoroughfare. Much of the recent load growth has occurred in the southeastern area of Gillespie County generally along and south of State Highway 290. The expansion of this highway, by the Texas Highway Department, is already underway within this growth area.




Figure 1: Map of Goehmann Lane Service Area

The Goehmann Lane Substation, located in Fredericksburg, contains two load-serving transformers with a combined winter capacity rating of 37.8 MVA. The total peak load supplied by the Goehmann Lane Substation reached 22.8 MW in winter 2011, and its

overall peak load reached 31.5 MW in winter 2010. This substation is radial-supplied by a 4-mile 69-kV transmission line tapped to the 0.8-mile Fredericksburg to Live Oak 69-kV transmission line.

Presently, approximately 43 percent of the total load served out of the Goehmann Lane Substation is located in the remote area to the southeast of Fredericksburg. There are no other substations immediately to the east of this area to provide back-up service (see Figure 1). The distance between the Goehmann Lane Substation and the most remote load, located in the southeastern most portion of CTEC's service area, is approximately 24 miles. As the load continues to increase, a corresponding decrease in reliability of service will impact a larger number of end-use customers due to the remoteness of the load to the source for transmission service to the area (existing Goehmann Lane Substation).

Transmission service to this broad area is limited to the CTEC 69-kV Goehmann Lane Substation. Over the last five years, CTEC and LCRA TSC have been working together to defer this type of project by shifting load to area substations. This includes the addition of load-serving transformers at the Gillespie, Hollmig and Nebo substations. In 2012, the Hollmig Substation, located west of the Goehmann Lane Substation, was placed in service to allow a permanent transfer of load from the Goehmann Lane Substation. This assisted in lowering the amount of load (end-use customers) that would lose electric service upon the loss of transmission service to the Goehmann Lane Substation. By 2016, the ability to defer the need for this type of project will be exhausted.

In terms of transmission service reliability, the total peak load supplied by Goehmann Lane Substation is projected to exceed 20 MW in 2019. This load level is reached after exhausting block load transfer opportunities by CTEC to the area substations (Hollmig and Nebo). This demand level of 20 MW exceeds the planning criteria thresholds used by LCRA TSC and CTEC for radial supplied load-serving substations.

The Fredericksburg-Live Oak-Goehmann Lane 69-kV transmission line, Goehmann Lane's sole transmission line source, has experienced 17 outages over the past nine years for a total outage time of over 24 hours. More recently, in February 2013 and April 2013, a failure in this sole transmission line source to the Goehmann Lane Substation resulted in the loss of electric service to 4000 end-use customers for more than two hours.

In terms of distribution service reliability, distribution system studies performed by CTEC revealed that the load of the two distribution feeders (Feeder #3 and #4) out of the Goehmann Lane Substation, which now supply the remote area load, will each exceed 6 MW in winter of 2013-2014. Continued load growth on the CTEC distribution system in this area, will exhaust available feeder capacities to such extremes that normal condition system performance will be threatened and reserve feeder capacity will not be available to respond to contingency conditions.