

# Filing Receipt

Received - 2022-11-08 11:07:19 AM Control Number - 54325 ItemNumber - 1

#### **Procedure for Certifying Renewable Energy Credit Generators**

- NOTE: Do not use this form if you intend to file for REC offsets or in association with a REC aggregation company. Contact the Commission to obtain the appropriate certification form.
- A. A completed application shall consist of the following.
  - 1. A completed Certification Form for Renewable Energy Credit Generators.
  - 2. A map showing the location of the facility and, if applicable, its boundary (for example, the boundary of the wind farm area metered at the point specified in Item 10). The map must also show the facility's interconnection point(s) with the local distribution or transmission system, and the location of all generation units listed under Item 13 of the application.
  - 3. If one or more of the metering points specified in Item 10 are not part of the transmission or distribution system of ERCOT, an Independent System Operator, a Regional Transmission Organization, or an Independent Organization as defined in PURA Section 39.151(b), a marrative explaining where and how the output of the facility may be physically metered and verified in Texas by the Program Administrator.
  - 4. For fossil fuels listed under Item 8, a narrative describing the role of such fuels in the generation technology. The narrative should explicitly state the heat input value of the fossil fuels relative to the heat input value of the renewable fuels specified in Item 7, and must include references to industry standards.
  - 5. For previously existing renewable energy units that were upgraded and repowered at a greater capacity after Sept. 1, 1999, a narrative specifying the shutdown date, restart date, previous rated nameplate capacity, and new rated nameplate capacity, including references to industry standards.
- B. Each certification shall pertain to a single facility. A facility may have multiple metering points, which shall be designated under Item 10. The metering points listed must represent the only locations through which generation from units included in the certification may enter an ISO grid.
- C. If a facility includes units that separately would be ineligible to produce RECs the application must include a number or formula approved by the Commission that permits the Program Administrator to subtract the output of such units from the aggregated output recorded at the metering point in Item 10.
- D. If an existing renewable energy unit is upgraded and repowered after Sept. 1, 1999, the unit must be included **twice** under Item 13. One entry shall designate the pre-upgrade rated nameplate capacity. The other shall show the **difference** between the new capacity and the pre-upgrade capacity and shall show the repower date as the date commercial operation begins / began.

- E. Item 11 shall be the generation of all units listed under Item 13 that have been included in a nomination for REC offsets.
- F. Eligible units are those which
  - 1. Are not fossil fuel units that have been repowered to use a renewable fuel,
  - 2. Were not developed as part of an emissions reduction project described in Health and Safety Code §382.05193, that is being used to satisfy the permit requirements in Health and Safety Code §382.0519,
  - 3. Are not included in the rates of any utility, municipally owned utility or distribution cooperative through base rates, a power cost recovery factor, stranded cost recovery mechanism or any other fixed or variable rate element charged to end users, and
  - 4. Are not capacity that was in operation before Sept. 1, 1999 unless the nameplate capacity is less than 2 MW.
- G. The owner's designated representative and alternate representative must be based in Texas.
- H. The owner of a facility certified to produce RECs may amend an existing application package if the facility's output is metered by an ISO. Amendment may be made by certified letter to the Commission describing the changes to be reflected in the facility's REC certification. If the amendment results in material change to the facts represented in any narrative or map submitted with the original application, updated narratives and maps must be included with the letter requesting the amendment. Narratives and maps that do not require revisions need not be resubmitted.

If the capacity of the facility changes at a later date, the owner of the facility shall file with the Commission any updated information on the facility by the 15<sup>th</sup> of the month following the end of the calendar quarter. The information filed shall reflect the change in nameplate capacity of the facility during the quarter just completed and the total capacity of the facility as of the last business day of the calendar quarter.

J. The owner of the facility shall provide the annual historical output of the facility (in MWh) from the start of commercial operations up to the date of filing this application. The annual period for historical output shall be from October 1 through September 30.

## **Certification Form for Renewable Energy Credit Generators**

### Information about Generating Unit(s)

1.	Facility Name or Description	Ganado Solar, LLC
2.	Street Address or Legal Geographical Location	962 County Road 260 Ganado, TX 77962
3.	Name of Owner	Ganado Solar, LLC
4.	Owner PUC Registration (for Subst. Rule §25.109)	20659
5.	On-site Contact Person (if applicable)	
6.	On-site Telephone Number (if applicable)	
7.	Type of Renewable Generating Technology	Biomass     Hydroelectric       X     Solar     Wind       Other (specify):     V
8.	Fossil Fuels Used ( <i>if any</i> )	
9.	TNRCC Air Permit Number ( <i>if any</i> )	
10.	Meters (ISO Numbers or Other Identifiers)	M1 WSL_MET1 WSL_MET2
11.	Percentage to be Subtracted from Annual Metered Generation	0
12.	Metered Generation Eligible for Renewable Energy Credits (in MW)	152.25MW

13.	Please complete the following Include additional pages as ne units, complete the attachment enter "See attached list" in the upgraded and repowered after the upgrade, and another page resulting from the upgrade.	for each generating unit opera cessary. For sites with large nu centitled "List of Generating U first three blanks of this section Sept. 1999, include one page describing the incremental ad	ating at this facility. umbers of individual Jnits at Facility" and on. For older units describing the unit before dition to capacity
	Manufacturer	see attached lis	t
	Serial Number(s)	see attached lis	t
	Date Commercial Operation Began / Will Begin	12/1/2022	
	Total Rated Nameplate Capacity	208.4MWdc	
	Is this a fossil fuel unit that ha to use a renewable fuel?	s been or will be repowered	YesNoX
	Is this unit developed as part of project described in Health and that is being used to satisfy the Health and Safety Code §382.	of an emissions reduction d Safety Code §382.05193, e permit requirements in 0519?	YesNoX
	If the generating unit is owned utility, an electric cooperative, competitive retailer, or river an this unit's above-market costs utility, municipally owned util cooperative through base rates factor, stranded cost recovery fixed or variable rate element of	by or under contract to a municipally-owned utility, athority, is any portion of included in the rates of any ity or distribution , a power cost recovery mechanism or any other charged to end users?	YesNoX
	If the answer is "yes" at the da state the date when the answer Provide documentation to supp	te this application is filed, would become "no." port this change of status.	Date
	Does this unit qualify for Rene Offsets?	ewable Energy Credit	YesNoX

Name, Mailing Address and Telephone of Generating Facility Owner Ganado Solar, LLC c/o Enel Green Power, NA 100 Brickstone Square Suite 300 Andover, MA 01810

Name, Mailing Address and Telephone of Owner's Designated Representative Ganado Solar, LLC c/o Enel Green Power, NA 100 Brickstone Square Suite 300 Andover, MA 01810 Attn: Jennifer Reilly

Name, Mailing Address and Telephone of Alternate Representative

Ganado Solar, LLC c/o Enel Green Power, NA 100 Brickstone Square Suite 300 Andover, MA 01810

I certify that I have reviewed and will comply with the provisions in Section 14, "Renewable Energy Credit Trading Program" of the ERCOT Protocols. I certify that the information presented in this Certification Form is correct. I further certify that the generating facility owner (or designated representative) shall inform the Project Administrator of any change that renders the information contained in this certification obsolete, and that such notification will be provided in writing no later than 30 days after the change is discovered by the owner.

# **Jennifer Reilly**

11/08/2022

**Owner of Generating Facility or Designated Representative** 

Date

## List of Generating Units at Facility

Manufacturer and Make	Serial Number(s)	Date Commercial Operation Began/Begins	Capacity per Unit (in MW)	Number of Units	Capacity (in MW)
see attached list	see attached list	12/1/2022	3.80625	40	152.25

The following files are not convertible:

Ganado Serial numbers.xlsx

Please see the ZIP file for this Filing on the PUC Interchange in order to access these files.

Contact centralrecords@puc.texas.gov if you have any questions.



YSTEM II         POI:         MVA:         E (KV):         VOLTAGE (KV)         VOLTAGE (KV)         SITE INF         ATURE:         ATURE:         DE:         MC         ACTURER:         DEL #:         SE (VV):         ING (V):         STRING:         TY (535W):         TY (545W):         INGS:         NG:         INGS:         NG:         INGS:         NG:         INCE         ACTURER:         OLL #:         S'C:         'PV 6         AGE (VDC):         /OLTAGE (KV):         ANTITY:	NFOR         150         176         138         34.5         208.43         FORM/         37.6°C         29.118         -96.518         DULLE         TRINA         TSM-DE         37         ARRA         38,961         231,620         114,737         10,414         NEGAT         SMA         SMA         10,600         4.40         3.96         1500         0.660         40	MATIC ATION ATION 3 EG19C.20 0, & 545 AY 0 7 IVE ER C 4400-UP				
POI:         POI:         MVA:         E (KV):         I VOLTAGE (KV)         I VOLTAGE (KV)         SITE INF         ATURE:         ATURE:         E:         DE:         MC         ACTURER:         DEL #:         SE (W):         ING (V):         STRING:         PV /         TY (535W):         TY (545W):         INGS:         NG:         INGS:         NG:         INCE         ACTURER:         ODEL #:         i°C:         AGE (VDC):         /OLTAGE (KV):         ANTITY:	150         176         138         34.5         208.43         CORM/         37.6°C         -3.4°C         29.118         -96.518         DULE         TRINA         1500         37         ARR/         1500         37         ARR/         1500         37         ARR/         535, 54/         1500         37         ARRA         SMA         SMA         10,414         NEGAT         SMA         114,737         10,660         4.40         3.96         1500         0.660         40	ATION ATION B EG19C.20 10, & 545 AY D 7 IVE ER C 4400-UP				
FOI.         INVA:         E (KV):         I VOLTAGE (KV)         I VOLTAGE (KV)         SITE INF         ATURE:         ATURE:         E:         DE:         ACTURER:         DEL #:         SE (VV):         ING (V):         STRING:         TY (535W):         TY (545W):         INGS:         NG:         INGS:         NG:         INGS:         NG:         INCE         ACTURER:         ODEL #:         i°C:         AGE (VDC):         /OLTAGE (KV):         ANTITY:	130         176         138         34.5         208.43         CRM/         37.6°C         -3.4°C         29.118         -96.518         DULE         TRINA         1500         37         ARR/         1500         37         ARR/         1500         37         ARR/         535, 540         138,961         231,620         114,737         10,414         NEGAT         SMA         SMA         10,660         4.40         3.96         1500         0.660         40	ATION ATION B EG19C.20 0, & 545 VY 0 7 IVE ER C 4400-UP				
MVA:         E (KV):         I VOLTAGE (KV)         I VOLTAGE (KV)         SITE INF         ATURE:         ATURE:         E:         DE:         MC         ACTURER:         DEL #:         SE (VV):         ING (V):         STRING:         PV /         TY (535W):         TY (545W):         INGS:         NG:         INGS:         NG:         INGS:         NG:         INCE         ACTURER:         OEL #:         i°C:         OEL #:         i°C:         AGE (VDC):         /OLTAGE (KV):         ANTITY:	176         138         34.5         208.43         CRM/         37.6°C         -3.4°C         29.118         -96.518         DULE         TRINA         1500         37         ARR/         1500         37         ARR/         1500         38,961         231,620         114,737         10,414         NEGAT         SMA         SMA         1500         11500         4.40         3.96         4.40         3.96         4.40         3.96         4.40	ATION ATION B EG19C.20 0, & 545 AY TVE ER C 4400-UP				
E (KV): I VOLTAGE (KV) SITE INF SITE INF ATURE: ATURE: ATURE: DE: MC ACTURER: DEL #: SE (VV): ING (V): STRING: PV / TY (535W): TY (545W): TY (545W): INGS: NG: INVE ACTURER: OEL #: SC: DEL #: SC: AGE (VDC): AGE (VDC): /OLTAGE (KV): ANTITY: TTY (FOULTAGE (KV): ANTITY: ANTITY: TTY (FOULTAGE (KV): ANTITY: TTY (FOULTAGE (FOULTAGE (KV): ANTITY: TTY (FOULTAGE (FOULTAGE (KV): ANTITY: TTY (FOULTAGE (FOU	138         34.5         208.43         ORM/         37.6°C         -3.4°C         29.118         -96.518         DULE         TRINA         TSM-DE         535, 54/         1500         37         ARR/         38,961         231,620         114,737         10,414         NEGAT         SMA         SMA         SMA         1500         10,660         40         \CKE	ATION ATION B EG19C.20 0, & 545 AY TVE ER C 4400-UP				
VOLTAGE (KV)   SITE INF   SITE INF   ATURE:   ATURE:   E:   DE:   MC   ACTURER:   DEL #:   SE (W):   ING (V):   STRING:   TY (535W):   TY (545W):   INGS:   NG:   INGS:   NG:   INGS:   NG:   ACTURER:   ODEL #:   i°C:   of C:   AGE (VDC):   AGE (VDC):	34.5         208.43         C         37.6°C         -3.4°C         29.118         -96.518         DULLE         TRINA         TSM-DE         535, 540         1500         37         ARRA         1500         38,961         231,620         114,737         10,414         NEGAT         SMA         SMA         SMA         1500         10.660         40         LOGO	ATION ATION ATION B C 19C.20 0, & 545 AY C 4400-UP C 4400-UP				
SITE INF SITE INF ATURE: ATURE: ATURE: DE: MC ACTURER: DEL #: SE (W): ING (V): STRING: PV / TY (535W): TY (545W): TY (545W): TY (545W): INGS: NG: INCE ACTURER: ODEL #: SC: DEL #: CC: AGE (VDC): AGE (VDC): ANTITY: TTY (FURCE)	208.43 <b>C</b> RM/ 37.6°C -3.4°C 29.118 -96.518 <b>DULE</b> TRINA TSM-DE 535, 540 1500 37 <b>ARR</b> / 38,961 231,620 114,737 10,414 NEGAT <b>ERTE</b> SMA SMA SO 4.40 3.96 1500 4.40 <b>SMA SO</b> 4.40	ATION ATION ATION C 4400-UP				
SITE INF SITE INF ATURE: ATURE: DE: DE: MC ACTURER: DEL #: DEL #: DEL #: DEL #: STRING: TY (535W): TY (535W): TY (545W): TY (545W): TY (545W): TY (545W): INGS: NG: INVE ACTURER: DEL #: ODEL #: ODEL #: ODEL #: C: AGE (VDC): AGE (VDC): ANTITY: TT A A A A A A A A A A A A A A A A A A	208.43 FORM/ 37.6°C 29.118 -96.518 DULLE DULLE 535, 544 1500 37 ARR/ 38,961 231,620 114,737 10,414 NEGAT ERTE SMA SMA SO 4.40 3.96 1500 4.40 3.96 4.40 3.96	ATION ATION ATION ATION A A A A A A A A A A A A A A A A A A A				
SITE INF ATURE: ATURE: ATURE: DE: DE: MC ACTURER: DEL #: DEL #: DEL #: STRING: TY (535W): TY (535W): TY (545W): TY (545W): TY (545W): TY (545W): INGS: NG: INVE ACTURER: DEL #: ODEL #: ODEL #: ODEL #: C: AGE (VDC): AGE (VDC): AGE (KV): ANTITY: TT A	ORM/         37.6°C         -3.4°C         29.118         -96.518         DULLE         TRINA         TSM-DE         535, 540         1500         37         ARRA         38,961         231,620         114,737         10,414         NEGAT         SMA         SMA SO         4.40         3.96         1500         0.660         40	ATION ATION ATION ATION A A A A A A A A A A A A A A A A A A A				
ATURE: ATURE: ATURE: ATURE: DE: MC ACTURER: DEL #: DEL #: DEL #: DEC TY (535W): TY (535W): TY (545W): TY (545W): INGS: NG: INCE ACTURER: DEL #: ODEL #: ODEL #: ODEL #: ODEL #: C: AGE (VDC): AGE (VDC): ANTITY: TT / C	37.6°C         -3.4°C         29.118         -96.518         DULLE         TRINA         TSM-DE         535, 540         1500         37         ARRA         38,961         231,620         114,737         10,414         NEGAT         SMA         SMA         SMA SO         4.40         3.96         1500         0.660         40	3 EG19C.20 .0, & 545 AY 0 7 IVE ER C 4400-UP				
ATURE: ATURE: ATURE: DE: DE: MC ACTURER: DEL #: SE (W): TING (V): STRING: PV / TY (535W): TY (545W): TY (545W): TY (545W): INGS: NG: INVE ACTURER: DEL #: SC: DEL #: SC: AGE (VDC): AGE (VDC): ANTITY: TT / C	37.6°C         -3.4°C         29.118         -96.518         DULLE         TRINA         TSM-DE         535, 540         1500         37         ARRA         38,961         231,620         114,737         10,414         NEGAT         SMA         SMA         SMA SO         4.40         3.96         1500         0.660         40	3 EG19C.20 ∴0, & 545 AY 0 7 <sup>1</sup> IVE ER C 4400-UP				
ATURE: PE: DE: MC ACTURER: DEL #: DEL #: DEL #: STRING: TY (535W): TY (535W): TY (545W): TY (545W): INGS: NG: INGS: NG: INCE ACTURER: DEL #: 'C: DEL #: 'C: AGE (VDC): AGE (VDC): ANTITY: TT / C	-3.4°C 29.118 -96.518 DULLE TRINA TSM-DE 535, 54 1500 37 <b>ARR</b> 38,961 231,620 114,737 10,414 NEGAT 231,620 114,737 5MA 5MA SMA SMA SMA SMA SMA SMA SMA SMA SMA S	3 EG19C.20 .0, & 545 AY 0 7 IVE ER C 4400-UP				
DE: DE: MC ACTURER: DEL #: DEL #: DEL #: TY (535W): TY (535W): TY (545W): TY (545W): INGS: NG: INCE ACTURER: DEL #: 'C: DEL #: 'C: AGE (VDC): AGE (VDC): ANTITY: TT / C	29.118 -96.518 DULLE TRINA TSM-DI 535, 54 1500 37 <b>ARRA</b> 38,961 231,620 114,737 10,414 NEGAT 231,620 114,737 5MA 5MA SMA SMA SMA 5MA 5MA 5MA 5MA 5MA 5MA 5MA 5MA 5MA 5	3 EG19C.20 .0, & 545 AY 0 7 IVE ER C 4400-UP				
DE: MC ACTURER: DEL #: DEL #: DEL #: TY (545W): TY (545W): TY (545W): TY (545W): TY (545W): INGS: NG: INCE ACTURER: DEL #: ODEL #: ODEL #: ODEL #: ODEL #: C: DEL #: ODEL #:	-96.518 DULLE TRINA TSM-DI 535, 544 1500 37 CRRA 38,961 231,620 114,737 10,414 NEGAT CRTE SMA SMA S0 4.40 3.96 1500 0.660 40 CREE	3 EG19C.20 -0, & 545 				
MC ACTURER: DEL #: DEL #: DEL #: DEL #: TY (535W): TY (535W): TY (545W): TY (545W): INGS: NG: INVE ACTURER: DEL #: PC: AGE (VDC): AGE (VDC): ANTITY: TT A	DULE TRINA TSM-DI 535, 54 1500 37 <b>ARRA</b> 38,961 231,620 114,737 10,414 NEGAT <b>ERTE</b> SMA SMA SO 4.40 3.96 1500 0.660 40	EG19C.20 40, & 545 <b>AY</b> 0 7 TIVE ER C 4400-UP				
ACTURER: DEL #: DEL #: DEL #: DEL #: TY (535W): TY (535W): TY (545W): TY (545W): INGS: NG: INVE ACTURER: DEL #: PC: AGE (VDC): AGE (VDC): ANTITY: TTC A	TRINA         TRINA         TSM-DI         535, 54         1500         37         ARRA         38,961         231,620         114,737         10,414         NEGAT         SMA         SMA S0         4.40         3.96         1500         0.660         40	EG19C.20 10, & 545 TVE ER C 4400-UP				
ACTURER: DEL #: DEL #: TING (V): STRING: PV / TY (535W): TY (545W): TY (545W): INGS: NG: INGS: NG: INVE ACTURER: DEL #: PC: AGE (VDC): /OLTAGE (KV): ANTITY: TT / /	TRINA         TSM-DI         535, 54         1500         37 <b>ARRA</b> 38,961         231,620         114,737         10,414         NEGAT <b>ERTE</b> SMA         SMA SO         4.40         3.96         1500         0.660         40 <b>ACKE</b>	EG19C.20 40, & 545 <b>AY</b> 0 7 TIVE <b>ER</b> C 4400-UP				
DEL #: SE (W): TING (V): STRING: PV / TY (535W): TY (545W): TY (545W): INGS: NG: INGS: NG: INVE ACTURER: DEL #: i°C: i°C: AGE (VDC): /OLTAGE (KV): ANTITY: TT / /	TSM-DI 535, 54 1500 37 <b>ARRA</b> 38,961 231,620 114,737 10,414 NEGAT <b>ERTE</b> SMA SMA SO 4.40 3.96 1500 0.660 40	EG19C.20 10, & 545 <b>AY</b> 0 7 TIVE <b>ER</b> C 4400-UP				
E (W): ING (V): STRING: PV / TY (535W): TY (545W): INGS: NG: INGS: NG: INVE ACTURER: DEL #: i°C: i°C: AGE (VDC): /OLTAGE (KV): ANTITY: TT / /	535, 54 1500 37 <b>ARR/</b> 38,961 231,620 114,737 10,414 NEGAT <b>ERTE</b> SMA SMA SO 4.40 3.96 1500 0.660 40 <b>ARKE</b>	4 Y 0 7 <sup>−</sup> IVE <b>ER</b> C 4400-UP				
TING (V): STRING: PV / TY (535W): TY (540W): TY (545W): INGS: NG: INGS: NG: INVE ACTURER: DEL #: ;°C: ;°C: AGE (VDC): /OLTAGE (KV): ANTITY: <b>TTO ^</b>	1500 37 <b>ARR</b> / 38,961 231,620 114,737 10,414 NEGAT <b>ERTE</b> SMA SMA SO 4.40 3.96 1500 0.660 40 <b>ACKE</b>	AY 0 7 TIVE ER C 4400-UP				
STRING: PV / TY (535W): TY (540W): TY (545W): INGS: NG: INGS: NG: INVE ACTURER: DEL #: ;°C: ;°C: /°C: AGE (VDC): /OLTAGE (KV): ANTITY: <b>TTO ^</b>	37 ARR/ 38,961 231,620 114,737 10,414 NEGAT ERTE SMA SMA SO 4.40 3.96 1500 0.660 40 ACKE	<b>AY</b> 0 7 TIVE <b>ER</b> C 4400-UP				
PV / TY (535W): TY (540W): TY (545W): INGS: NG: INGS: NG: INVE ACTURER: DEL #: OLTAGE (KV): ANTITY: TD ^	<b>ARR/</b> 38,961         231,620         114,737         10,414         NEGAT <b>ERTE</b> SMA         SMA SO         4.40         3.96         1500         0.660         40 <b>LCKE</b>	AY 0 7 TIVE ER C 4400-UP				
<b>PV</b> <i>F</i> TY (535W): TY (540W): TY (545W): INGS: NG: <b>INVE</b> <b>ACTURER:</b> DEL #: j°C: DEL #: j°C: AGE (VDC): /OLTAGE (KV): ANTITY: <b>TT N</b>	38,961         231,620         114,737         10,414         NEGAT <b>ERTE</b> SMA         SMA         4.40         3.96         1500         0.660         40	- Y 0 7 1VE ER C 4400-UP				
TY (535W): TY (540W): TY (545W): INGS: NG: INVE ACTURER: DEL #: j°C: AGE (VDC): /OLTAGE (KV): ANTITY: T C ^	38,961 231,620 114,737 10,414 NEGAT <b>ERTE</b> SMA SMA SO 4.40 3.96 1500 0.660 40 <b>\CKE</b>	0 7 <sup>-</sup> IVE <b>ER</b> C 4400-UP				
TY (540W): TY (545W): INGS: NG: INVE ACTURER: DEL #: j°C: AGE (VDC): /OLTAGE (KV): ANTITY: TD ^	231,620 114,737 10,414 NEGAT <b>ERTE</b> SMA SMA SO 4.40 3.96 1500 0.660 40 <b>\CKE</b>	0 7 TIVE <b>ER</b> C 4400-UP				
TY (545W): INGS: NG: INVE ACTURER: DDEL #: j°C: J°C: AGE (VDC): /OLTAGE (KV): ANTITY: TD ^	114,737 10,414 NEGAT <b>ERTE</b> SMA SMA SC 4.40 3.96 1500 0.660 40	7 TIVE <b>ER</b> C 4400-UP				
INGS: INGS: INGS: ACTURER: DDEL #: S°C: S°C: AGE (VDC): /OLTAGE (KV): ANTITY: TD ^	114,737 10,414 NEGAT ERTE SMA SMA SC 4.40 3.96 1500 0.660 40 \CKE	, TIVE ER C 4400-UP				
INGS: NG: INVE ACTURER: DEL #: ODEL #: ODEL #: ODEL #: ODEL (VDC): AGE (VDC): AGE (VDC): ANTITY: ANTITY:	10,414 NEGAT <b>ERTE</b> SMA SMA SC 4.40 3.96 1500 0.660 40 <b>CKE</b>	TIVE ER C 4400-UP				
NG: ACTURER: DEL #: S°C: S°C: S°C: AGE (VDC): AGE (VDC): ANTITY: ANTITY: TD A	NEGAT ERTE SMA SMA SC 4.40 3.96 1500 0.660 40 ACKE	TIVE ER C 4400-UP				
INVE ACTURER: DDEL #: DDEL #: ODEL #:	ERTE SMA SMA SC 4.40 3.96 1500 0.660 40 40	ER c 4400-UP				
ACTURER: DDEL #: S°C: S°C: AGE (VDC): /OLTAGE (KV): ANTITY: ANTITY:	SMA SMA SC 4.40 3.96 1500 0.660 40 40	C 4400-UP				
ACTURER: DDEL #: S'C: S'C: C: AGE (VDC): AGE (VDC): AGE (KV): ANTITY: ANTITY: ANTITY:	SMA SMA SO 4.40 3.96 1500 0.660 40 <b>\CKE</b>	C 4400-UP				
DDEL #: 5°C: 'AGE (VDC): /OLTAGE (KV): ANTITY: <b>TD ^</b>	SMA S( 4.40 3.96 1500 0.660 40 <b>\CKE</b>	C 4400-UP				
5°C: P°C: AGE (VDC): /OLTAGE (KV): ANTITY: <b>TD ^</b>	4.40 3.96 1500 0.660 40 <b>\CKE</b>					
'AGE (VDC):         /OLTAGE (KV):         ANTITY:	3.96 1500 0.660 40 <b>\CKE</b>					
AGE (VDC): /OLTAGE (KV): ANTITY:	1500 0.660 40 <b>\CKE</b>					
/OLTAGE (KV): ANTITY:	0.660 40 <b>\CKE</b>					
	<b>\</b> CKE					
IKA		R				
 JRER	ATI					
)FC).						
·						
TION:	1-HIGH	PORTAIT				
_E LIMITS:	52°±					
) TRACKER QTY:	3,313					
) TRACKER QTY:	237					
	3 550					
(ГТ):	35.15%	wizz.25				
RADE (FT)	5.5					
-						
					T	
			-		<u> </u>	
		JO	R	WM	<b></b> _	NCB
		4/01/22 PREPARED	4/0 CH	J1/22 IECKED	4/ A	/01/22
~				)	•	
U.	JHINA	רח אר אר אר		<b>k</b>		
JACKSO	N COUNTY,	. I X & WHART		ι Υ, ΤΧ 		
04012	:022_GA	NADO_N	EI_AO	)5R1		
	FORMAT:	: SCALE	: P	LOT SCALE:	S	HEET:
DN:						-/-
DN:		I	I		I	
	TITLE:					
DN: COPE:	TITLE:			QITE I	LAYO	UT
DN: COPE:		E01-04 O	/ERAL			ł
DN: COPE:	TITLE:	E01-04 O'	/ERAL			
DN: COPE:	TITLE:	E01-04 O	/ERAL			
DN: COPE: IN TYPE ISSUER C	JUNTRY TEC.	EGP CODE			PROGRESSIVE	'E REVISION
-	NSTRUCTION TION JACKSC 04012 DN:	NSTRUCTION TION GANA JACKSON COUNTY, 04012022_GA DN: FORMAT COPE: TITLE:	NSTRUCTION J0 4/01/22 TION PREPARED GANADO SC JACKSON COUNTY, TX & WHART 04012022_GANADO_N DN: FORMAT: SCALE	NSTRUCTION J0 R 4/01/22 4/0 PREPARED CH GANADO SOLAR JACKSON COUNTY, TX & WHARTON COUN 04012022_GANADO_NEI_A00 DN: FORMAT: SCALE: F COPE: TITLE: E01_04_OVERAL	NSTRUCTION          J0       RVM         4/01/22       4/01/22         ION       PREPARED       CHECKED         GANADO SOLAR         JACKSON COUNTY, TX & WHARTON COUNTY, TX         04012022_GANADO_NEI_A005R1         DN:       FORMAT:       SCALE:         PLOT SCALE:         COPE:       TITLE:         E01-04 OVERALL SITE	J0       RWM         VSTRUCTION       J0         4/01/22       4/01/22         ION       PREPARED         CHECKED       A         JACKSON COUNTY, TX & WHARTON COUNTY, TX         04012022_GANADO_NEI_A005R1         DN:       FORMAT:         SCALE:       PLOT SCALE:         SCOPE:       TITLE:         E01-04 OVERALL SITE LAYO

1.2124

1.2079

1.2533

1.2533

1.2533

1.2533

1.3577

1.0671

1.0353

1.0217

1.2533

1.2533

1.2533

1.2533

1.2533

1.2942

1.2896

1.3169

1.2442

1.3078

1.2578

1.1579

1.3759

1.2192

1.1787

1.2012

1.1382

1.1687

1.3061

0.9762

1.0403

1.0862

0.9487

0.9899

0.9578

1.1091

1.2649

1.1045

1.1595

1.0999